# Ultimate Protection Against Wind, Air and Moisture.

PRO

PROLin

1-800-000-0000 www.website.com

PROLinx

# BlueLinxCo.com

Commercial grade for severe weather.

PROLinx

PROL

PRO



PROL inv

PROL

# *Our premium, mid-perm protection outperforms the competition.*

Breathable and easy-to-install, ProLinx<sup>®</sup> Advantage Plus is a non-perforated, non-woven, permeable membrane with unique smart-perm technology that reduces inward vapor solar drive for uncompromising protection from the effects of harsh weather.



# Benefits:

PRO

PROLinx

PROLin

PROL

PROLinx

1-800-000-0000

• **Higher performance** Building wraps made of non-perforated membranes offer the highest level of performance against wind, air, and moisture.

PRO

PRO

PRO

PROL

- **Breathable Membrane** If moisture gets trapped in the walls, it can destroy the integrity of your insulation. Our unique, micro-porous, "breathable" membrane allows moisture vapor to pass through without becoming trapped in the wall cavity to provide the utmost in air and moisture control.
- **Surfactant resistant** Not affected by pressure washing, jobsite chemicals, or sugars from tree sap and wood sidings, unlike some other products.
- **Superior strength** Its non-perforated, non-woven polyolefin composition gives ProLinx<sup>®</sup> Advantage Plus superior strength.
- Longer UV Resistance Special ultraviolet stabilizers protect it from the sun's harsh rays. In fact, ProLinx<sup>®</sup> Advantage Plus is protected against UV rays for up to 9 months.
- **Designed translucence** ProLinx<sup>®</sup>Advantage Plus can be installed right over the sheathing, and because you can see through it, it makes framing members easy to find.
- **Recognized as an air barrier** Compliant with IRC and IBC as an air barrier.

# Warranty Information

A ten (10) year limited warranty applies to PROLinx<sup>®</sup> Advantage+ building wrap. To obtain a copy of this warranty, please visit bluelinxco.com. No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

## Standard Roll Sizes\*

 9' x 100'
 9' x 150'
 9' x 195'

 10' x 100'
 10' x 150'
 10' x 195'

 \*Custom sizes available upon request. Not all rolls available for digital printing

# World-class building wrap. Localized service.

With a broad geographic footprint servicing 50 states, BlueLinx has branches ready to fulfill your order. Our expert representatives know the geography of the markets you're working in, and product delivery is never far away. PROLinx<sup>®</sup> can be delivered with other BlueLinx products for your convenience.

#### Specifications

Property	Standard
CSI ID Code	Air Barriers 07270
Composition	Non-Perforated Non-Woven Polyolefin
Perm Rating	ASTM E-96A - 16 US Perms
Tensile Strength	ASTM D-5034 59 lbs/in. MD 51 lbs/in. CD
Flame Spread	ASTM E-84 Class A
UV Exposure Rating	9 months
Applicable Standards	Meets Fed. Spec. UU-B-790a Grade D

#### **10-Year Limited Warranty**

**Precautions** | *Warning:* Protect from high heat or other ignition sources during shipment, storage, and application.

**Storage** | Take care to protect PROLinx Building Wrap from exposure to direct sunlight during storage. It is recommended that building wrap to be stored inside or under cover.



# Increasing Your Brand Awareness Just Became Limitless!

# Maximize your brand's impact with ProLinx Building Wrap.

Dealers and builders can now promote their brand and attract local interest with state-of-the-art high resolution print technology.

## No Set-Up Fee:

Choose from a wide spectrum of colors and gradients at no extra cost.

## Alternating Messages & Images:

Impactful logos, custom messaging, and contact information all on one roll of any grade building wrap.

# Flexible Order Size:

Mix two custom logos on same pallet.



BlueLinxCo.com

Call your local BlueLinx representative to find out how custom printing can expand your business!