Reliable weather BlueLinxCo.com Professional contractor grade for moderate to protection. severe weather. PROLinx PROL PRO PRO PRO PRO 1-800-000-0000 1-800-000-0000 PROLI PRO PROL PRO PROLinx PROLin PROLIN PRO PROLinx PROLinx PROLinx PRO PROLinx PROLinx PRO PROLinx PRO

PROLinx[®] BUILDING WRAP Select

An unbeatable combination of value and performance.

Ideal for projects requiring reliable weather protection, PROLinx[®] Select balances breathability with a high level of water resistance. Easy to install, it's durable and strong due to woven fabric construction, making it a terrific value. PROLinx[®] Select is available with digital printing to display any logo or advertising message.



Benefits:

- **Higher Performance** Micro-perforations designed for maximum performance. We don't just punch holes in the material our perforations have been designed with the angle, size, and direction that offer maximum performance.
- **Resists Bulk Water** Resists water penetration from wind-driven rain and other sources.
- **Stops Solar Vapor Drive** Limits incoming moisture while allowing unwanted moisture to escape the wall cavity. This prevents the moisture from inward solar vapor drive from damaging the wall cavity.
- **Superior Strength** ProLinx[®] Select is made of a cross-woven polyolefin material known for its superior strength and tear-stop design.
- **UV Resistance** ProLinx[®] Select special ultraviolet stabilizers protect it from the sun's harsh rays. In fact, ProLinx[®] Select protects against UV rays for up to 12 months.
- **Designed Translucence** ProLinx[®] Select Wrap can be installed right over the sheathing and because you can see through it, it makes framing members easy to find.
- Wind and Tear Resistance Heavy winds pose a threat to house wrap during installation. With its tear-stop design, ProLinx[®] Select Wrap is one of the most durable wraps around.

Warranty Information

A ten (10) year limited warranty applies to PROLinx[®] Select building wrap. To obtain a copy of this warranty, please visit bluelinxco.com. No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

Standard Roll Sizes*

9' x 100' 9' x 150' 9' x 195' 10' x 100' 10' x 150' 10' x 195'

*Custom sizes available upon request. Not all rolls available for digital printing

World-class building wrap. Localized service.

With a broad geographic footprint servicing 50 states, BlueLinx has branches ready to fulfill your order. Our expert representatives know the geography of the markets you're working in, and product delivery is never far away. PROLinx[®] can be delivered with other BlueLinx products for your convenience.

Specifications

Property	Standard
Composition	Perforated Woven Polyolefin
Perm Rating	ASTM E-96A - 11 US Perms
Tensile Strength	ASTM D-5034 63 lbs/in. MD 51 lbs/in. CD
Flame Spread	ASTM E-84 Class A
UV Exposure Rating	12 months Applicable Standards: Meets Fed. Spec. UU-B-790a Grade D

10-Year Limited Warranty

Precautions | *Warning:* Protect from high heat or other ignition sources during shipment, storage, and application.

Storage | Take care to protect PROLinx[®] Building Wrap from exposure to direct sunlight during storage. It is recommended that building wrap to be stored inside or under cover.



Increasing Your Brand Awareness Just Became Limitless!

Maximize your brand's impact with ProLinx Building Wrap.

Dealers and builders can now promote their brand and attract local interest with state-of-the-art high resolution print technology.

No Set-Up Fee:

Choose from a wide spectrum of colors and gradients at no extra cost.

Alternating Messages & Images:

Impactful logos, custom messaging, and contact information all on one roll of any grade building wrap.

Flexible Order Size:

Mix two custom logos on same pallet.



BlueLinxCo.com

PROLinx Select / 07-2023

Call your local BlueLinx representative to find out how custom printing can expand your business!