



COVERPRO[®]3000

SYNTHETIC ROOFING UNDERLAYMENT



Extra Strength/Lightweight - #30 Felt Replacement

PRODUCT OVERVIEW

A much better choice than #30 felt... CoverPRO[®]3000 is the roofing professional's preference when the project demands the performance benefits often found in premium synthetic underlayment at the cost of 30 lb. roofing felt. Manufactured from 100% synthetic materials, CoverPRO 3000 offers the same dynamic walking surface, simple installation and easy to handle lightweight roll as CoverPRO and the addition of a specially formulated low slip bottom side coating. This layer adds strength and grabs the deck to reduce stress around fasteners and add a measure of safety. CoverPRO 3000's four layer construction is the professional's choice for use on steeper slopes under all types of roofing material; including: asphalt shingles, synthetic shingles, cedar shakes, and metal. Safer and stronger than 30 lb. felt with more installation and installed performance benefits than other professional grade products, a 30-year Limited Warranty and extra-large full color Broadcast[®] custom printed advertising makes CoverPRO 3000 the Pro's choice for your next project.

FEATURES

SAFER: Asphalt saturated felt can be slippery and potentially unsafe underfoot and slide on the roof deck; CoverPRO 3000's proprietary non-woven walking surface and specially engineered low slip bottom side coating improves roof deck walkability in all conditions.

EASIER: Each 10 square roll weighs less than 26 lbs. and is attached with standard roof nails (plastic caps not needed), so getting CoverPRO 3000 on the roof and attached is simple, less expensive and fast.

STRONGER: CoverPRO 3000's unique four layer construction makes it 20 times stronger than 30 lb. roofing felt. It requires significantly fewer fasteners and provides a tough, durable deck cover regardless of weather conditions.

GRAY COLOR: Provides a comfortable working surface in all temperatures and an excellent background for your extra large (up to 30" tall/unlimited width) full color custom printed logo, phone number, web site or other advertisement.

ADVERTISE: Bigger and bolder with Broadcast Custom Print – the easiest way to get leads or earn paid advertising revenue during your project. With Broadcast Custom Print your individual logo, phone number, web address and any other advertisements can be featured on the same roll, with individual images more than 2 feet tall and 10 feet wide. Broadcast Custom Print offers the largest, most vivid job site advertising in the industry.

FEATURES AND BENEFITS:

- 20x stronger and 5x more coverage per roll than 30 lb. roofing felt
- 11% more coverage per course than traditional 30 lb. felt
- 30 Year Limited Warranty (see website for warranty details)
- Non-woven walking surface feels like traditional felt underfoot
- Sure footing with a deck grabbing low slip bottom side coating
- Less weight per roll means easier handling during installation
- Sustainability – may contribute to LEED and NGBP ratings
- Superior lay-flat properties; will not wrinkle or absorb water
- Cool Gray color is engineered to reduce heat build-up
- Remains flexible and easy to install in cold climates
- 100% synthetic construction – will not rot or mold
- 90 Day UV exposure rating
- Class A fire rating

TYPICAL PHYSICAL PROPERTIES

| PROPERTY & STANDARD | CoverPRO 3000 TYPICAL RESULT | ASTM #30 FELT TYPICAL RESULT |
|-------------------------------|------------------------------|------------------------------|
| Permeability ASTM E96 | 0.1 perms | 1.75 perms |
| Water Transmission ASTM D4869 | Pass | Pass |
| Tear Strength ASTM D4533 | MD 38 lbs / CD 37 lbs | MD 4 lbs / CD 2 lbs |
| Tensile Strength ASTM D751 | MD 120 lbs / CD 115 lbs | MD 70 lbs / CD 38 lbs |
| Burst Strength ASTM D751 | 160 psi | 62 psi |
| Elongation ASTM D751 | 20% | 2% |
| Weight per Square ASTM D5261 | 2.46 lbs | 27.5 lbs |
| Nominal Thickness ASTM D1777 | 7.5 mils | 60 mils |
| Temperature Range – Internal | -70 F to 240 F | No value offered |

Results reflect typical properties of control/non-conditioned specimens. Values should not be interpreted as limiting specifications and will vary within typical manufacturing tolerances

COVERPRO 3000 PACKAGE SPECIFICATIONS

- Roll Dimensions 40" x 300'
- Weight per Roll 25.6 lbs
- Coverage per Roll 10 sq
- Rolls per Pallet 42
- Pallet Weight 1375 lbs

CODE & STANDARD COMPLIANCE

- ICC-ES AC188 (ESR-1293)
- ASTM D226 Type I & II
- ASTM D4869
- CSA A 123.3 Type 1 & 2
- FBC #8700-R2
- Texas Dept. of Insurance (TDI)



COVERPRO[®]3000
SYNTHETIC ROOFING UNDERLAYMENT

©2015 System Components Corporation. All rights reserved.
CoverPRO is a trademark of System Components Corporation.

Phone: 425-392-5150 (West) | 330-528-0255 (East)
Email: support@systemcomponents.net
Web: www.systemcomponents.net

System Components Corporation
P.O. Box 2432
Issaquah, WA 98027

CoverPRO[®] 3000 PRODUCT INFORMATION
LAST UPDATED 7/16/2015