




# WeatherLock® Mat

Self-Sealing Ice & Water Barrier



Designed to act as a secondary water barrier under asphalt shingles, wood shakes and quarry slate roof assemblies, WeatherLock® Mat Self-Sealing Ice & Water Barrier helps prevent damage due to shingle blow-off, wind-driven rain and ice damming.

- Acts as another line of defense when used on the entire roof deck, and is a best roofing practice for entire roof deck coverage on 2:12 to 4:12 pitch roofs to help keep water out from under shingles
- Ideal for all underlayment applications such as full roof deck coverage, eaves, rakes and valleys
- Patented mat-faced design provides for consistent surface—reducing slipping, sticking and scuffing
- 40% lighter than competitive products, making it easier to load, carry and install



**WeatherLock® Mat**  
Self-Sealing Ice & Water Barrier



## The essentials for a healthy roofing system.

It takes more than just shingles to create a high-performance roof. It requires a system of products working together. Owens Corning™ Roofing Essentials™ Accessory Products work with our shingles to make up a roofing system that helps provide maximum durability for your roof. And the most protection for your home.

- a** VentSure® Ventilation Products
- b** PINK™ Fiberglas™ Blown-In Insulation
- c** Owens Corning™ Hip & Ridge Shingles
- d** Owens Corning™ Shingles
- e** Owens Corning™ Underlayment Products
- f** WeatherLock® Self-Sealing Ice & Water Barrier Products
- g** Owens Corning™ Starter Shingle Products
- h** RapidFlow® Gutter Drainage Protection
- i** Owens Corning™ Undereave Ventilation Products



**OWENS CORNING**  
**ROOFING AND ASPHALT, LLC**  
 ONE OWENS CORNING PARKWAY  
 TOLEDO, OHIO, USA 43659

1-800-GET-PINK™  
[www.roofing.owenscorning.com](http://www.roofing.owenscorning.com)

Pub. No. 58107-F. Printed in U.S.A. November 2010.  
 THE PINK PANTHER™ & © 1964–2010 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. ©2010 Owens Corning.



## Construction

### Surface

Polymeric asphalt surface

### Interior Reinforcement

Durable Fiberglas® mat

### Adhesive Styrene

Mixture of Styrene-Butadiene-Styrene (SBS) and asphalt

### Removable Backing

Split-sheet peel-away poly backer

### Application

Engineered for asphalt shingles, wood shakes and quarry slate roof assemblies

## Typical Values\*\*

Property	1 sq. roll	2 sq. roll
Length	33.3 ft. (10.2 m)	66.7 ft. (21.3 m)
Width	3 ft. (.91 m)	3 ft. (.91 m)
Area	100 sq. ft. (9.3 m <sup>2</sup> )	200 sq. ft. (19.4 m <sup>2</sup> )

## Applicable Standards and Codes

ICC ESR 1783

ASTM D 1970

Uniform Building Code Tables 15B-1, 15B-2, 15D-1 and 15D-2

UL Class A, Class C

Florida Building Code

Miami-Dade County Approved†

## Physical Properties

Property	Test Method	Typical Values**
Thickness	—	48 mils
Slip Resistance	Asphalt Saturated Felt	Passed
Pliability	1" Mandrel Bend at -20°F	Passed
Tensile Strength	ASTM D 412	—
Longitudinal (md)	—	48 lbs./in.
Transverse (cd)	—	35 lbs./in.
Elongation at Break (modified bitumen portion)	ASTM D 2523	250%
Permeance	ASTM E 96	.05 max.
Adhesion to Plywood, 40°F	ASTM D 903	1.0 lbs./in.
Adhesion to Plywood, 75°F	ASTM D 903	6.0 lbs./in.
Tear Resistance	ASTM D 4037	—
Longitudinal	—	20 lbs.
Transverse	—	20 lbs.
Sealability around Nail	ASTM D 1970	Passed
Low Temperature Flexibility	ASTM D 1970	Passed
Waterproofing Integrity after Low Temperature Flex	ASTM D 1970	Passed
Waterproofing Integrity of Lap	ASTM D 1970	Passed

\*Ensure proper ventilation is met when applied over the entire roof deck.

\*\*All values are approximate.

†Applies for all areas that recognize Miami-Dade County Building Code.