





Premium Building Products  
That Protect

# Tile Flash 30XL/ 60XL

**Exposable  
Peel and Stick  
Wind & Rain Block  
Hip & Ridge Detail  
for use under  
Roof Tile**



**ICC #ESR1825 Approval Report**  
Meets the Roof Tile Institute, Issue #01-701



## Tile Flash 30XL/60XL Advantages:

- Features a black film facer
- Available in 30 or 60 mils thick
- Self-adhering tape adheres and seals to the contours of the tile roof
- Available in 9" and 12" widths for low and high profile tile
- SBS modified rubberized asphalt adhesive has superior technology, resiliency, and longevity over common Butyl-type adhesives
- All-weather, can be exposed to the elements
- UV Resistant
- Pressure Sensitive Adhesion
- 10 Year Limited Warranty
- Internal Aluminum
- Moldable SBS Membrane is pliable and has excellent conformability characteristics
- Meets the Roof Tile Institute, Issue #01-701 Recommendations for Weather Blocking on Flat, Low, and High Profile Concrete and Clay Roof Tiles

**Description:**

**TILE FLASH 30XL/60XL** is an exposable, self-adhering, cold-applied tape used as flashing on concrete or clay hip and ridge roofing tiles. **TILE FLASH 30XL/60XL** is a pressure-sensitive tape manufactured from bituminous and synthetic resins. This tape is faced with an **aluminum coated black film** on one side and is backed with a release film that protects the adhesive and prevents the product from sticking to itself.

**Application:**

For best results, be sure tile surface to be sealed is clean, dry and free of any other contaminant that may adversely affect adhesion.

Cut **TILE FLASH 30XL/60XL** to desired length and peel off release liner from bottom, taking care not to allow the adhesive to come into contact with itself or any foreign matter.



Center the material on the ridge of hip board and loosely lay the tape so there is a slight sagging down into the pans of the tile.



Premium Building Products  
That Protect

**DO NOT STRETCH TILE FLASH 30XL/60XL.**

Proceed by carefully conforming **TILE FLASH 30XL/60XL** to the contours of tile profile pressing and smoothing the tape to maximize contact to 100% of the tile surface. Pressure is essential to eliminate any wrinkles or trapped air bubbles. Overlaps should be a minimum of 2 inches on side lap, and 4 inches on end lap.

**Precautions:**

Caulk must not be used in conjunction with **TILE FLASH 30XL/60XL**.

Uncured vinyl products may have an adverse chemical reaction with **TILE FLASH 30XL/60XL**.

**Standard Sizes:**

Standard Size/Rolls per Case/Weight per Case (lbs.)/  
Cases per Pallet

9" x 50'/4/72 lbs./24

12" x 50'/4/96 lbs./18

**PROTECTO WRAP COMPANY**

1955 South Cherokee Street

Denver, Colorado 80223

(303) 777-3001

(800) 759-9727

(303) 777-9273 FAX

[www.protectowrap.com](http://www.protectowrap.com)