



is the finest in the industry. It turns passersby into an audience, and a building into a billboard – a vivid, multi-colored multi-messaging

platform with endless revenue generating possibilities. BROADCAST® custom printing leads the industry with the following features:

Full Color:

A full range of vivid colors.

Maximum-size:

The largest printing area available.

Alternating Messages & Images:

Select multiple messages for your building wrap.

Flexible Order Size:

Orders as small as 9 rolls, and as large as needed.

Visit our WRAPLAB® at

prolinx.customprintwrap.com

Call our experts at **(888) 502-BLUE** to find out how customer printing can expand your business!



Typical Physical Properties

Property	Standard	UoM	Typical Result ¹
Basis Weight	ASTM D 5261	g/m ²	72
Breaking Strength (MD/CD)	ASTM D 882	lbs/inch	30/30
Drainage Efficiency ²	ASTM E 2273	% Efficiency	95
Water Vapor Transmission Rate	ASTM E 96, Method A	g/m ² /24 hours	392
Water Vapor Permeance	ASTM E 96, Method A	perms	56
Water Penetration Resistance	AATCC 127	cm H ₂ O	186
Water Resistance	ASTM D 779	minutes	60
Air Resistance	ASTM E 2178	L/sec/m ² @ 75 Pa	< 0.02
Flame Spread Index	ASTM E 84	Class	A
Smoke Developed Index	ASTM E 84	Class	A
Ultraviolet Light (UV) Exposure	Internal	Days	120

¹ Results reflect typical properties of control/non-conditioned specimens. Values should not be interpreted as limiting specifications and will vary within typical manufacturing tolerances.

² PROLinx Drain Building Wrap demonstrates compliance with Exception 1, Section 703.1.1 of the 2011 Oregon Residential Specialty Code as a Water-Resistant Barrier with enhanced drainage and exceeding 75% drainage efficiency when tested in accordance with ASTM E2273.

WARRANTY INFORMATION

A ten- (10-) year limited warranty applies to **PROLinx® Drain** building wrap. To obtain a copy of this warranty, please visit BlueLinxCo.com or call **888-502-BLUE**. No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

PRECAUTIONS

Warning: Protect from high heat or other ignition sources during shipment, storage and application.

STORAGE

Take care to protect PROLinx building wrap from exposure to direct sunlight during storage. It is recommended that building wrap to be stored inside or under cover.

ROLL SIZES*

3' x 100', 4.5' x 100', 5' x 100', 9' x 100', 10' x 100',
3' x 150', 4.5' x 150', 5' x 150', 9' x 150', 10' x 150',
9' x 195', 10' x 195'

*Not all rolls available for BROADCAST custom printing, ask your sales representative for more details.

Drain



Enhanced drainage capability for severe weather.

PROLinx®
BUILDING WRAP

Drain



YOUR BARRIER OF PROTECTION AGAINST THE ELEMENTS.

PROLinx
BUILDING WRAP
Drain

PROLinx BUILDING WRAP	<i>Select</i>	<i>Drain</i>	<i>Advantage</i>	<i>Plus LP</i>	<i>Plus HP</i>
Meets Building Code	☑	☑	☑	☑	☑
Energy Efficient	☑	☑	☑	☑	☑
Optimal UV Resistance	☑	☑	☑	☑	☑
Superior Tear Strength	☑	☑	☑	☑	☑
BROADCAST™ Custom Printing	☑	☑	☑	☑	☑
Enhanced Drainage Capability		☑			
Certified Air Barrier	☑	☑	☑	☑	☑
More Robust Water Resistance		☑	☑	☑	☑
10-Year Limited Warranty	☑	☑	☑	☑	☑



PROLinx® Drain is designed for severe weather protection, maximum drainage, and balanced breathability under fiber-cement, brick, vinyl, stucco, hardboard, metal, stone, and wood sidings. It promotes drainage in all directions for faster, more complete drying and easy installation. PROLinx Drain is UV-stabilized and may be left exposed for up to 120 days. To learn how to transform your PROLinx Drain into a multi-colored, multi-messaging space with endless revenue-generating possibilities, visit our custom printing page!

PROLinx Drain is available with BROADCAST® custom printed advertising. Now you can custom print PROLinx Drain in full color with alternating messages in the industry's smallest minimum quantities.

Drainage Barrier: PROLinx Drain combines the benefits of a rainscreen and building wrap to promote moisture movement away from the wall.

Durable Drainage Surface: PROLinx Drain's durable drainage surface does not collapse or flatten when siding is installed.

Breathable: PROLinx Drain demonstrates superior resistance to weather and allows for the highest transfer of moisture vapor, ideal for projects requiring building wraps having a high level of vapor permeability.

Energy Efficiency: PROLinx Drain complies with IECC requirements for air barrier materials, contributing to greater energy efficiency in residential and commercial projects.

Meets Building Codes: PROLinx Drain is rated for commercial projects. It meets or exceeds applicable building codes for water-resistant barriers and drainage rates, creating a healthy, energy-efficient building.

Stable: PROLinx Drain is treated to resist excessive degradation from normal exposure to ultraviolet light and may be left exposed for up to 120 days.

PROLinx Flashing and Sheathing Tapes are also available. 10-Year Limited System Warranty

Broadcast and Wrplab are registered trademarks of Jumpstart Consultants, Inc.

1-888-502-BLUE | www.BlueLinxCo.com

BlueLinx
America's Building Products Distributor