

Premium high permeability protection against the elements.

BlueLinxCo.com



Professional contractor grade for moderate to severe weather.



PROLinX[®] BUILDING WRAP *Plus HP*

Severe weather demands a serious defense.

Breathable and easy-to-install, ProLinX[®] Plus HP is a non-perforated, non-woven, permeable membrane with unique smart-perm technology that reduces inward vapor solar drive for uncompromising protection from the effects of harsh weather.

Benefits:

- **Higher performance** Building wraps made of non-perforated membranes offer the highest level of performance against wind, air and moisture.
- **Breathable Membrane** If moisture gets trapped in the walls, it can destroy the integrity of your insulation. Our unique, micro-porous, “breathable” membrane allows moisture vapor to pass through without becoming trapped in the wall cavity to provide the utmost in air and moisture control.
- **Surfactant resistant** Not affected by pressure washing, jobsite chemicals, or sugars from tree sap and wood sidings, unlike some other products.
- **Superior strength** Its non-perforated, non-woven polyolefin composition gives ProLinX[®] Plus HP superior strength.
- **Longer UV Resistance** Special ultraviolet stabilizers protect it from the sun’s harsh rays. In fact, ProLinX[®] Plus HP is protected against UV rays for up to 9 months.
- **Recognized as an air barrier** Compliant with IRC and IBC as an air barrier.

BLUELINX
DELIVERING WHAT MATTERS™

Warranty Information

A ten(10) year limited warranty applies to PROLinx® Plus HP building wrap. To obtain a copy of this warranty, please visit bluelinxco.com. No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

Standard Roll Sizes*

9' x 100' 9' x 150' 9' x 195'
10' x 100' 10' x 150' 10' x 195'

*Custom sizes available upon request. Not all rolls available for digital printing

World-class building wrap. Localized service.

With a broad geographic footprint servicing 50 states, BlueLinx has branches ready to fulfill your order. Our expert representatives know the geography of the markets you're working in, and product delivery is never far away. PROLinx® can be delivered with other BlueLinx products for your convenience.

Specifications

Property	Standard
CSI ID Code	Air Barriers 07270
Composition	Non-Perforated Non-Woven Polyolefin
Perm Rating	ASTM E-96A - 50 US Perms
Tensile Strength	ASTM D-5034 59 lbs/in. MD 51 lbs/in. CD
Flame Spread	ASTM E-84 Class A
UV Exposure Rating	9 months
Applicable Standards	Meets Fed. Spec. UU-B-790a Grade D

10-Year Limited Warranty

Precautions | **Warning:** Protect from high heat or other ignition sources during shipment, storage, and application.

Storage | Take care to protect PROLinx® Building Wrap from exposure to direct sunlight during storage. It is recommended that building wrap to be stored inside or under cover.

PROLinx[®]
BUILDING WRAP *Plus HP*

BlueLinxCo.com
PROLinx Plus HP / 07-2023



Increasing Your Brand Awareness Just Became Limitless!

Maximize your brand's impact with PROLinx Building Wrap.

Dealers and builders can now promote their brand and attract local interest with state-of-the-art high resolution print technology.

No Set-Up Fee:

Choose from a wide spectrum of colors and gradients at no extra cost.

Alternating Messages & Images:

Impactful logos, custom messaging, and contact information all on one roll of any grade building wrap.

Flexible Order Size:

Mix two custom logos on same pallet.

Call your local BlueLinx representative to find out how custom printing can expand your business!