



is the finest in the industry. It turns passersby into an audience, and a building into a billboard – a vivid, multi-colored multi-

messaging platform with endless revenue generating possibilities. BROADCAST® custom printing leads the industry with the following features:

**Full Color:**

A full range of vivid colors.

**Maximum-size:**

The largest printing area available.

**Alternating Messages & Images:**

Select multiple messages for your building wrap.

**Flexible Order Size:**

Orders as small as 10 rolls, and as large as needed.

Visit our WRAPLAB® at [prolinx.customprintwrap.com](http://prolinx.customprintwrap.com)

Call our experts at **(888) 502-BLUE** to find out how customer printing can expand your business!



**Typical Physical Properties**

Property	Standard	UoM	Typical Result <sup>†</sup>
Basis Weight	ASTM D 5261	g/m <sup>2</sup>	90
Breaking Tensile Strength (MD/CD)	ASTM D 882	lbs/inch	71/50
Water Vapor Transmission Rate	ASTM E 96, Method A	g/m <sup>2</sup> /24 hours	84
Water Vapor Permeance	ASTM E 96, Method A	perms	12
Water Penetration Resistance	AATCC 127	cm H <sub>2</sub> O	500
Water Resistance	ASTM D 779	minutes	60
Water Ponding	ASTM E 2556, A 1.1	Pass/Fail	Pass
Air Resistance	ASTM E 2178	L/sec/m <sup>2</sup> @ 75 Pa	0.01
Flame Spread Index	ASTM E 84	Class	A
Smoke Developed Index	ASTM E 84	Class	A
Ultraviolet Light (UV) Exposure	Internal	Days	180

<sup>†</sup>Test data is based on average results and is not limiting specifications. Normal manufacturing variation may produce results above or below typical data and should not be considered or interpreted as minimum or maximum values.

**WARRANTY INFORMATION**

A ten- (10-) year limited warranty applies to PROLinx® Advantage building wrap. To obtain a copy of this warranty, please visit [BlueLinxCo.com](http://BlueLinxCo.com) or call **888-502-BLUE**. No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

**PRECAUTIONS**

**Warning:** Protect from high heat or other ignition sources during shipment, storage and application.

**STORAGE**

Take care to protect PROLinx building wrap from exposure to direct sunlight during storage. It is recommended that building wrap to be stored inside or under cover.

**ROLL SIZES\***

3' x 100'	3' x 150'	4.5' x 100'	4.5' x 150'
5' x 100'	5' x 150'	9' x 100'	9' x 150'
9' x 195'	10' x 100'	10' x 150'	10' x 195'

\*Not all rolls available for BROADCAST custom printing, ask your sales representative for more details.

Advantage



Commercial grade for severe weather.



**BlueLinx**  
**1-888-502-BLUE**  
[www.BlueLinxCo.com](http://www.BlueLinxCo.com)

**BlueLinx**

# YOUR BARRIER OF PROTECTION AGAINST THE ELEMENTS.

**PROLinX**  
BUILDING WRAP  
**Advantage**

<b>PROLinX</b> BUILDING WRAP	<b>Select</b>	<b>Drain</b>	<b>Advantage</b>	<b>Plus LP</b>	<b>Plus HP</b>
Meets Building Code	☑	☑	☑	☑	☑
Energy Efficient	☑	☑	☑	☑	☑
Optimal UV Resistance	☑	☑	☑	☑	☑
Superior Tear Strength	☑	☑	☑	☑	☑
BROADCAST™ Custom Printing	☑	☑	☑	☑	☑
Enhanced Drainage Capability		☑			
Certified Air Barrier	☑	☑	☑	☑	☑
More Robust Water Resistance		☑	☑	☑	☑
10-Year Limited Warranty	☑	☑	☑	☑	☑



**PROLinX® Advantage** is a commercial-grade building wrap, engineered from non-perforated cross woven fabrics. Providing the highest real-world resistance to severe weather and wind driven rain, it is well-suited for demanding residential and commercial projects.

**PROLinX Advantage** is a recognized air barrier material that allows for a balanced transfer of moisture vapor, creating a healthier and more energy-efficient structure.

**PROLinX Advantage** is available with BROADCAST® custom printed advertising. Now you can custom print **PROLinX Advantage** in full color with alternating messages in the industry's smallest minimum quantities.

**Strength:** PROLinX Advantage provides maximum durability with high resistance to tearing.

**Industry Leading Weather Protection:** PROLinX Advantage exhibits class-leading resistance to moisture and limits air movement within the wall cavity.

**Breathability:** PROLinX Advantage is engineered to slow inward moisture vapor drive more than higher breathing building wraps.

**Energy Efficiency:** PROLinX Advantage complies with IECC requirements for air barrier materials, contributing to greater energy efficiency in residential and commercial projects.

**Simple Application:** Lightweight, yet durable, PROLinX Advantage is translucent which makes locating studs, openings, and corners quick and easy.

**Meets Building Codes:** PROLinX Advantage is rated for commercial projects and offers excellent performance in residential applications. It meets or exceeds applicable building codes for water-resistant barriers and air barriers, creating a healthier, more energy-efficient building.

**UV Exposure Rating:** PROLinX Advantage has a 50% longer UV exposure rating than other building wrap brands, and may be left exposed or up to 180 days.

**PROLinX Flashing and Sheathing Tapes are also available. 10-Year Limited System Warranty**

Broadcast and Wraplab are registered trademarks of Jumpstart Consultants, Inc.

1-888-502-BLUE | [www.BlueLinXCo.com](http://www.BlueLinXCo.com)

**BlueLinX**  
America's Building Products Distributor