



PREMIUM BUILDING PRODUCTS
THAT PROTECT

Protecto Tarp

"The Storm Chaser"



Used as a Temporary Roof covering for storm protection, can be applied over existing roof coverings that have been damaged from storms for temporary protection, can be left exposed for up to 6 months. Will adhere to OSB, plywood, shingles, concrete and clay tile, smooth BUR, fascia board, trim, metal flashing, drip edge and many other substrates.

Is a cold applied, self-adhering membrane composed of a proprietary slip resistant, tri-layer, woven polyolefin fabric coated on one side with a layer of high temperature recycled asphalt/butyl hybrid adhesive.

APPLICATION:

Install **Protecto Tarp** starting at the lowest point of roof slope and work up the slope. Position the roll into the desired location, roll out the membrane and cut to length as needed.

Align the roll with edge of eave or overlap of preceding roll, pull membrane tight, start by removing a 12" to 24" portion of the release liner and adhere to roof (reposition as needed prior to removing the remaining release liner). Lift the opposing end of the membrane and remove or strip the release liner, pulling it to one side, keep membrane aligned and tight, adhere membrane to the roof while another person brooms the sheet flat.



Protecto Tarp can also be installed vertically over the roof starting at the eave and extending over the ridge if needed. In this type of application, **Protecto Tarp** shall extend a minimum 12" over the ridge.

Extended exposure to extreme hot weather and UV may cause some shrinkage, it is important to maintain the minimum overlap recommendations, side laps are 6" minimum and end laps are 12" minimum. All laps should be firmly pressed or rolled to ensure a positive seal.

Protecto Tarp can be mechanically fastened if needed at the perimeter edge using 1 1/4" minimum cap nails. If **Protecto Tarp** is lapped over the edge of the roof, it is recommended that the vertical edges be mechanically fastened.



PREMIUM BUILDING PRODUCTS
THAT PROTECT



Protecto Tarp

"The Storm Chaser"

Used as a Temporary Roof covering for storm protection, can be applied over existing roof coverings that have been damaged from storms for temporary protection, can be left exposed for up to 6 months. Will adhere to OSB, plywood, shingles, concrete and clay tile, smooth BUR, fascia board, trim, metal flashing, drip edge and many other substrates.

Protect Tarp is a cold applied, self-adhering membrane composed of a proprietary slip resistant, tri-layer, woven polyolefin fabric coated on one side with a layer of high temperature recycled asphalt/butyl hybrid adhesive.

Properties	Test Method	Test Results
Surface Color		Green
Thickness		25 mils
Tensile Strength	ASTM D412	>1600 psi
Elongation (adhesive only)	ASTM D412	500%
Puncture Resistance	ASTM E154	>250 psi
Low Temp Flex	ASTM D1970	No cracks or delamination at 0° F
UV Exposure period		6 months
Operating Temperature		Up to 250°F (up to 121°C)
Permeance	ASTM E96	<.05

FEATURES AND BENEFITS:

- Proprietary RECYCLED asphalt/butyl hybrid adhesive.
- 6 month UV exposure rating.
- Fully adhered system.
- Proprietary slip resistant surface for footing safety.
- Seals around properly installed fasteners.
- Waterproof, Air and Vapor Barrier.
- Can be installed Horizontally or Vertically.
- Available in 72" x 40' rolls at 40 lbs/roll
- Protect your property and contents from further storm damage.
- Feel confident that your family and home have excellent temporary protection until full repairs can be completed.
- Allows sufficient time to coordinate repairs with your insurance company and contractors without risking the possibly damage which can occur by installing a loose "blue tarp".