



# PRODUCTS LISTING

## BT25XL Window and Door Sealing Tape

A tough-faced superior self-adhering, air/vapor barrier and waterproofing membrane for vertical and horizontal above grade substrates. BT25XL seals window perimeters to building substrates to create an impenetrable barrier.

- Meets or exceeds all building codes including ASTM 2112 and ICC Code Approval ESR 1825
- Adheres to vinyl, plywood, OSB, foam, metal, aluminum and masonry
- Can be left exposed up to 120 days



## Super Stick Building Tape

A high tack, tenacious, durable, peel and stick air/vapor barrier tape system used for sealing PVC and aluminum fin windows and doors; window and door openings; and as a full coverage air vapor barrier membrane.

- No primer needed
- Can be installed in extremely cold or hot conditions
- Can be applied to damp surfaces
- 12-month UV Exposure
- Passes proposed AAMA 700 Sealant/Flashing compatibility testing
- Will not react with plasticizers



## Deck Joist Tape/Joist Seal Tape

- Protects joists from wood rot damage due to water infiltration
- Creates a corrosion barrier between ACQ/AC2 treated lumber and non ACQ/AC2 approved metal surfaces
- Use of Protecto Deck Flashing/Anti-Corrosion Tape as a ledger board flashing eliminates moisture between the house and ledger board
- UV Resistant



## Roof Edge Seal

A double-sided, internally reinforced peel and stick membrane designed to bond the roof covering edge to the roof.

- All temperature adhesive allows for application in all climates
- Low profile 40 mil thickness will not telegraph through the roof covering
- Quick and easy to install
- Evaluation report IAPMO ER #390 and Florida Building Code FL17155



## Jiffy Seal® Ice & Water Guard HT 25


A cold applied, self-adhering membrane composed of a proprietary slip resistant, tri-layer, woven polypropylene fabric coated on one side with a layer of high temperature asphalt/recycled butyl hybrid adhesive.

- 6 month UV exposure rating
- Tri-Layer, Engineered Film Technology
- Waterproof, Air and Vapor Barrier
- Can be installed Horizontally or Vertically (as code allows)
- Can be installed on roof pitches down to 2"/12"



## Dual Guard Threshold Tape™

- Exceeds all building codes and manufacturers installation specifications
- Helps stop air, moisture and bug infiltration under the threshold
- Adheres to concrete, wood and metal surfaces
- Helps prevent sub-floors from swelling and structural framing from warping
- Helps stop entry/patio doors from racking and costly call backs for additional adjustments
- 100% waterproof, mold and mildew resistant
- Designed for all entry/patio doors.



Call your local BlueLinX representative at  
800-830-7370 to learn more or visit [ProtectoWrap.com](http://ProtectoWrap.com)

Distributed by

