

# Premium Grade Synthetic Roof Underlayment

BlueLinXCo.com



## PROLinX®

UDL PRO

### Outperforms the competition.

ProLinX UDL Pro is suitable for all roof coverings and offers a 20-year limited warranty, backed by high-performance features that benefit both builders and homeowners.

### Benefits:

- **UV resistance** Special ultraviolet stabilizers protect it from the sun's harsh rays for up to 180 days.
- **Water Resistance** Protection against water elements, ensuring a strong, protective, and reliable installation.
- **Non-skid coating** ProLinX® UDL Pro has a non-skid coating for safe installation.
- **Ease of installation** Lies flat and doesn't wrinkle.
- **More coverage means faster installation** 48-inch width means faster installation and savings on labor costs.
  - 14% more coverage per lap (48-inch width compared to 42-inch synthetics)
  - 33% more coverage per lap (48-inch width compared to 36-inch felt)
- **Superior Wind & Tear Resistance** Heavy winds pose a threat to roof underlayment during installation. With its tear-resistant design, ProLinX® UDL Pro is a superior & durable underlayment.

**BLUELINX**  
DELIVERING WHAT MATTERS™



## Warranty Information

A twenty (20) year limited warranty applies to PROLinx® Synthetic UDL Pro. To obtain a copy of this warranty, please visit [bluelinxco.com](http://bluelinxco.com). No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

## Specifications

Meets Standards	ASTM D226 I & II ASTM 4869 II & IV FL #16453-R5	
Standard Sizes	48" x 125' 48" x 250'	12 lbs/roll 23 lbs/roll
Water Transmission	ASTM D4869	Pass
Water Vaport Transmission	ASTM E96 0.07 US Perms	
Tensile Strength	ASTM D828 75 lbs/in. MD 40 lbs/in. CD	
Nominal Thickness	ASTM D1777	8 mils
UV Exposure	6 months	

## Preparation

The deck surface must be dry and free of dust, dirt, loose nails, debris, and other protrusions. Damaged sheathing must be replaced. Ensure that the space beneath the roof sheathing is properly ventilated before installing to avoid condensation problems.

## Installation

ProLinx® Synthetic UDL Pro is laid out horizontally (parallel) to the eave, with the printed side up, using 4" horizontal laps and 6" vertical laps. Follow codes for low slopes as defined as 2:12 to 4:12 and steep slopes greater than 4:12 applications. ProLinx® UDL Pro is designed to withstand 30 days of exposure prior to being covered with the final roofing material. BlueLinx recommends covering ProLinx® UDL with the final roofing material as soon as possible.

## Fasteners

Attach ProLinx® Synthetic UDL Pro to structural roof deck material using plastic cap, ring shanked roofing nails that have a minimum 1" diameter cap. Anchoring to be installed at a minimum per surface markings, spaced 6" on-center in vertical and horizontal laps, and 12" on-center along the center of the roll. If the application of ProLinx® UDL Pro and the final roofing material occur on the same day, then the option to use every other printed anchoring placement is acceptable. For same day coverage, corrosion resistant 38" head and 1" leg roofing nails are acceptable as well as 1" plastic cap staples. High slope roofs, (> 7/12 pitch) must use plastic cap nails. All anchoring devices must be flush, 90° to the roof deck, and tight with the underlayment surface and the structural roof deck.

## Precautions

As with any roofing product, always follow safe roofing codes and practices (OSHA), and always use fall-protection devices when working on roofs (i.e. toe boards, rope harnesses, and rubber or synthetic soft-sole footwear). Use caution when walking or standing on ProLinx Synthetic UDL Pro as wet and/or dusty conditions may reduce traction. Failure to use proper safety gear and footwear can result in serious injury.



For application instructions, visit [BlueLinxCo.com](http://BlueLinxCo.com)

[BlueLinxCo.com](http://BlueLinxCo.com)

PROLinx UDL Pro / 06 - 2023



## Increasing Your Brand Awareness Just Became Limitless!

### World-class underlayment. Localized service.

With a broad geographic footprint servicing 50 states, BlueLinx has branches ready to fulfill your order. Our expert representatives know the geography of the markets you're working in, and product delivery is never far away. PROLinx® can be delivered with other BlueLinx products for your convenience.

### Maximize your brand's impact with PROLinx Building Wrap.

Dealers and builders can now promote their brand and attract local interest with state-of-the-art high resolution print technology.

### No Set-Up Fee:

Choose from a wide spectrum of colors and gradients at no extra cost.

### Alternating Messages & Images:

Impactful logos, custom messaging, and contact information all on one roll of any grade building wrap.

Call your local BlueLinx representative to find out how custom printing can expand your business!